

KORASILON® ÖI AF 4

Short description KORASILON® ÖI AF 4 is a non-reactive aminofunctional polydimethylsiloxane.

Product propertiesCharacteristic is the very good storage stability in ready-to-use formulations.

Processing KORASILON® ÖI AF 4 can be used as a water repellent in automatic car washes.

The effect is based on the neutralization with organic or inorganic acids, which converts **KORASILON®** Öl **AF 4** into the cationic form with high absorption capacity. The tearing behaviour and the lustre of gloss-drying agents are improved if combined with cation-active emulsifiers and surfactants, without causing an unwanted

product build-up in multiple applications.

KORASILON® ÖI AF 4 is also used in paint preservatives and paint polishes to increase the gloss and the resistance to detergents. The amino functionality of

KORASILON® ÖI AF 4 shows an excellent affinity for painted surfaces.

Product data* Appearance : clear liquid

Viscosity at 25 °C in mm²/s : ca. 25
Amine value in mmol/g : ca. 1.3
Refractive index : 1.4105

Storage KORASI KORASILON® ÖI AF 4 has a shelf life of 24 months after date of manufac-

turing when correctly stored in its original unopened container at storage tempera-

tures between +5 °C and +40 °C.

Storage beyond to the period indicated on the product label does not automatically mean that the product is unusable. However, an inspection of the property values necessary for the intended use is essential due to quality assurance reasons.

Further information on product safety and handling is given in the Material Safety Data Sheet.

This information and our technical advice – whether verbal, in writing or by way of trials – are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility.

Our products are sold in accordance with our General Conditions of Sale and Delivery; this is not valid for our trial products

*Informative properties not intended to be used as product specification

Kurt Obermeier GmbH, Berghäuser Str. 70, D-57319 Bad Berleburg Tel.: +49 (0) 2751/524-0, Fax.: +49 (0) 2751/5041, email: info@obermeier.de / www.obermeier.de