

KORASILON® Silicone Remover liquid

Short description	KORASILON® Silicone Remover liquid , Silicone remover based on an organic acid in solvent.
Product properties	KORASILON® Silicone Remover liquid acts as a chain destroyer in silicone rubber masses, in order to simplify the removal of hardened rubber.
Application	The silicone rubber is cutted out from the joints with a knife. In order to remove the adherent residue, KORASILON® Silicone Remover liquid is applied to the joint with a brush. After a dwell time, e. g. over night, of 3 to 20 hours (depending on the layer thickness) the joint is wiped clean of KORASILON® Silicone Remover liquid . Then the remaining residue is removed using a wet cloth. This is only an example of use for KORASILON® Silicone Remover liquid . In any case, the resistance of the substrate must be tested in an uncritical area.
Technical data*	Appearance : milky, white to yellowish Flash point : > 62 °C Active content in % (w/w) : approx. 20 Density : approx. 0.83 g/cm ³
Storage	KORASILON® Silicone Remover liquid has a shelf life of 24 months when stored between +5 °C und +40 °C in the tightly closed original container. The containers must be protected against direct sunlight. We recommend homogenizing the product prior to use. Storage beyond this period does not necessarily mean that the product is no longer usable. However, the properties required for the intended use must be checked for quality assurance reasons.

Further information on product safety and handling is given in the Material Safety Data Sheet.

This information and our technical advice – whether verbal, in writing or by way of trials – are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery; this is not valid for our trial products

*Informative properties not intended to be used as product specification

Kurt Obermeier GmbH & Co. KG, Berghäuser Str. 70, D-57319 Bad Berleburg, Germany Tel.: +49 (0)2751/524-0, Fax.: +49 (0)2751/5041, email: info@obermeier.de www.obermeier.de